

HEAVY DUTY RELAY

(H.I.D.) WR 6161



kameleon



- **Two-wire relay system used for monitoring and control**
- **Manual operation lever with ON/OFF indicator**
- **Reliable contact opening mechanism for flawless operation up to 1,500 amp for 20 milliseconds**
- **Optional auxiliary contact**

Input rating : 18 V AC to 30 V AC
Positive pulse = OFF action
Negative pulse = ON action

Ambient temperature : -30 °C to 50 °C

Electrical performance :
Resistive load 20 A, 347 V AC
Inductive load 20 A, 347 V AC
Incandescent lamp 2 400 W, 120 V AC
Fluorescent lamp 20 A, 347 V AC
H.I.D. lamp 20 A, 347 V AC

Test condition :
Switching cycle, 20 times/minute,
over 30,000 ON/OFF operation

Auxiliary contact (optional) : 1 A 125 V AC

Certification : ACNOR (CSA) and UL



gentec
ENERGY MANAGEMENT

www.gentec.ca

Gentec US

35 Gateway Drive, suite 302
Plattsburgh, New York
USA 12901
Tel.: 1-888-235-7506
Fax: (518) 793-2687
E-mail: ge@gentec.ca

Head Office

2625 Dalton Street
Sainte-Foy, Quebec
Canada, G1P 3S9
Tel.: 1-800-463-4480
Fax: (418) 651-6695
E-mail: ge@gentec.ca