

# PLUG-IN RELAYS

## WR 6321



kameleon



- **Two-wire relay system used for monitoring and control**
- **ON/OFF indicator**
- **Reliable contact opening mechanism for flawless operation up to 1,500 amp for 20 milliseconds**
- **35 mm rail-mount base**
- **Plug-in relay, easy to maintain**

Input rating : 18 V AC to 30 V AC  
Positive pulse = OFF action  
Negative pulse = ON action

Ambient temperature : -30 °C to 50 °C

Electrical performance :  
Resistive load 20 A, 347 V AC  
Inductive load 20 A, 347 V AC  
Incandescent lamp 2 400 W, 120 V AC  
Fluorescent lamp 20 A, 347 V AC

Test condition :  
Switching cycle, 20 times/minute,  
over 30,000 ON/OFF operation

Certification : ACNOR ( CSA ) and UL



**gentec**  
ENERGY MANAGEMENT

www.gentec.ca

### Gentec US

35 Gateway Drive, suite 302  
Plattsburgh, New York  
USA 12901  
Tel.: 1-888-235-7506  
Fax: (518) 793-2687  
E-mail: ge@gentec.ca

### Head Office

2625 Dalton Street  
Sainte-Foy, Quebec  
Canada, G1P 3S9  
Tel.: 1-800-463-4480  
Fax: (418) 651-6695  
E-mail: ge@gentec.ca